



Befestigung/ fastening/ fixation
 Draufsicht/ top view/ vue d'en houte

Seitliche Seilablenkung max. 4° zur Trommelachse
 max. side deviation angle 4° to drum
 max. Déviation de câble de max. 4° à l'axe du tambour

Seilzug- fähigkeit lifting force capacité levage daN	Hauptmaße in mm																	
	main dimensions in mm																	
	dimensions principales en mm																	
	D1	D2	B1	B2	H1	H2	H3	L1	L2	L3	L4	L5	L6	L7	L8	L9	HEB	Ø
1200	195	410	500	460	100	215	520	500	155	1400	405	630	80	540	80	20	100	14
2100	195	410	500	460	100	215	520	500	155	1500	405	730	80	540	80	20	100	14
2500	244	500	600	560	100	260	610	500	155	1500	405	720	80	550	80	20	100	14
4000	298	500	600	560	100	260	610	500	155	1600	405	820	80	550	80	20	100	14
5500	355	600	700	660	100	310	710	500	165	1900	415	1110	80	560	80	20	100	17
7000	406	700	800	750	120	360	830	500	200	1900	450	1055	100	560	100	25	120	19
9000	455	750	900	840	140	385	900	500	215	1950	465	1070	110	560	110	30	140	22
13000	470	850	1000	940	160	435	1020	500	259	2000	509	1050	120	590	120	40	160	26
16000	508	950	1100	1040	160	495	1130	500	259	2050	509	1100	120	590	120	40	160	26
20000	610	1100	1300	1230	180	570	1300	500	260	2100	510	1140	120	590	120	40	180	32
32000	660	1200	1500	1420	200	620	1420	500	299	2500	549	1490	140	590	140	40	200	36