

### APPLICATION

The stopfor™ KS 150kg is a sliding fall arrester of new-generation. It can be used with 11 mm diameter braided rope. The stopfor™ KS 150kg is a new fall arrest concept. Unlike fall arresters implementing a jaw as locking system, the stopfor™ KS 150kg eliminates the risk of mechanical blocking. Blocking is ensured by the body when an abrupt change of position occurs. For this reason, the unit is more ergonomic and compact than its competitors and slides easier on the rope with no excessive locking. The unit can be opened to allow the user to perform maintenance on the product with no need to disassemble. The stopfor™ KS 150kg is equipped of anti-reversibility system.



stopfor™ KS 150kg

### TECHNICAL CHARACTERISTICS

- Material: anodized aluminum
- Steel connector M10
- Designed for use with TRACTEL polyamide braided rope, 11mm diameter (sold separately)
- Bare weight: 192g

	Braided rope 11mm	Anti reversibility system	Park function	Aluminium flange	150kg	Vertical use	Horizontal use
stopfor™ KS 150KG	YES	YES	NO	YES	YES	YES	NO

### DESCRIPTION

The stopfor™ KS 150kg fall arrester is made of aluminum.

This light weight, robust, ergonomic and compact device connects to all the fall arrest anchoring points on the harness. It can be connected to the latter using a type M10 connector. The rope is easy and fast to set up. To do so, the user removes the connector, swivels the two side plates and positions the rope. To close the unit, the user simply pivots the two side plates in the opposite direction and reinstalls the connector which acts as a safety lock.

The stopfor™ KS 150kg is equipped of anti-reversibility system.

### NORMS

- EN 353.2
- CNB/P/11.062

### CODE

CODE	DESIGNATION	CODES STATS	EAN CODE
276279	stopfor™ KS 150kg M10	42110	3600232762799